

MODEL. PALLET-TURNER S-TURNER SD2000-15 / SD2400-15

TECHINCAL DATA:



| | | |
|--------------------|--|----------------------------|
| Capacity. | MAX. | 1500kg |
| High Capacity Max. | | 2000/2400mm |
| High Capacity Min | | 350mm |
| Platform dim. | | 1200*1200mm |
| Machine width. | 1600mm (SD2000 / 1800mm (SD2400) | |
| Machine length. | 2200mm (SD2000 / 2400mm (SD2400) | |
| Machine high. | 2400mm (SD2000 / 2800mm (SD2400) | |
| Machine Weight. | | 1300kg / 1600kg |
| Operation. | Manual Push-button/ Automatic HMI Screen | |
| Cycle time. | | Approx. 20-25 pallets/hour |
| Voltage. | | 400V - 3 faser + N + PE |



Samzon Pallet-Turner SD is a stationary pallet turner machine that runs to floor-level and is used to change pallets or for removing paper spacer or freezer spacer. The pallet is fed into the machine using a pallet truck or pallet jack. The machine can either rotate 90-degrees or 180-degrees depending on your needs. To remove paper spacer or freezer spacer, the machine is rotated from 0 to 90-degrees, pressure from the platforms is alleviated to allow for removal of spacers.

Changing pallets, either because of a defect pallet or swapping it to a plastic pallet, the new pallet is placed on top of the product, the platforms press down on the product, rotate 180-degrees, and the product is now standing on its new pallet. This does require manual pallet lifting, to place the new pallet on top - to avoid manual lifts a different type of pallet-inverter is recommended.

The pallet turner can be delivered with a variety of extra equipment and surface treatments.

MAX 2000mm - MIN 200mm
2383

1230,00
1600,00

2224

| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. |
|----------|----------------------------|-----------------------|------|
| 1 | 015-1178-1 | BUNDRAMME SVEJST | 1 |
| 2 | 015-1157-- | TÅRN S-TURNER | 1 |
| 3 | 015-1184-0 | DÆKSKÆRM | 1 |
| 4 | switch_xckd2118p16_ext-2.1 | --- | 4 |
| 5 | 015-0306-2.1 | Beslag for føler | 4 |
| 6 | VPRD0216 | --- | 1 |
| 7 | KS | --- | 2 |
| 8 | CE stik 400v-2415 | --- | 1 |
| 9 | 015-1338-0 | PLADE FOR FØLER | 4 |
| 10 | 015-1339-0 | PLADE FOR TILSLUTNING | 1 |
| 11 | 015-1343-- | PUMPE-STATION | 1 |

| | | |
|--|---|---|
| GENERELT HVIS USPECIFICERET: SE HVIS SÆRBEHØRER OVERFLADER TOLERANSE: 3.2/ | | UDBYTERE MODEL S-TURNER-2000-12-SD KOMPLÆT S-Turner New |
| RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION | RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION | RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION |
| RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION | RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION | RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION |

MAX 2400mm - MIN 400mm
2773,00

1280,00
1740,00

1285,00
2384

| ITEM NO. | PART NUMBER | DESCRIPTION | QTY. |
|----------|---------------------------------|-----------------------|------|
| 1 | 015-1626-1.13 | BUNDRAMME SVEJST | 1 |
| 2 | 015-1612--.13 | TÅRN S-TURNER | 1 |
| 3 | 015-1646-0.13 | DÆKSKÆRM | 1 |
| 4 | switch_xckd2118p16_ext-2.1.1.13 | --- | 4 |
| 5 | 015-0306-2.1.1.13 | Beslag for føler | 4 |
| 6 | KS.1.13 | --- | 2 |
| 7 | CE stik 400v-2415.1.13 | --- | 1 |
| 8 | 015-1338-0.1.13 | PLADE FOR FØLER | 4 |
| 9 | 015-1339-0.1.13 | PLADE FOR TILSLUTNING | 1 |
| 10 | 015-1643--.13 | PUMPE-STATION | 1 |

| | | |
|--|---|--|
| GENERELT HVIS USPECIFICERET: SE HVIS SÆRBEHØRER OVERFLADER TOLERANSE: 3.2/ | | UDBYTERE MODEL S-TURNER-SD2400-01 KOMPLÆT S-Turner 2400-15 New |
| RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION | RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION | RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION |
| RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION | RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION | RIEKSCONSTRUCTION RIEKSCONSTRUCTION RIEKSCONSTRUCTION |